

# HARDCORE RACERS:



“Traditional Needle-Roller Bearing and  
it’s small load distribution footprint.”



*Needles  
are  
old  
News!*

.... *ISKY's Revolutionary new wide-footprint/  
low friction **EZ-Roll**™ Bearing!*

For Extreme Conditions, ISKY's New



**\*EZ-ROLL™ Lifters ARE "NEEDLE FREE"!**

**EXTREME-LOAD RACING'S NEW STANDARD OF EXCELLENCE!**

**HARDCORE RACERS:**

For your environment, needles are old news! At ISKY, we've seen the future of roller lifter bearing development and it's NEEDLE FREE!

Introducing the revolutionary new **EZ-ROLL™** bearing option, exclusively for ISKY **RED-ZONE™** Roller Lifters! **EZ-ROLL™** "needle-free" roller bearings solve the age old dilemma of needle bearing overload. Although needle roller bearings perform well in light to moderately heavy load applications, the often extreme loading demands of "all out" drag, pro-street, continuous operation endurance and offshore marine applications have long



No Needles = No Problems!

required a better performing alternative. Solution: ISKY'S proprietary solid bearing raceway **EZ-ROLL™** Bearing! Spintron® and field test proven over the past 3 years, **EZ-ROLL™** bearings carry far greater loads. Their advanced needle-free design and greater surface area to load distribution footprint deliver a solid 350% higher load rating! **EZ-ROLL™**,... because needles really are old news!

The new **EZ-ROLL™** bearing option is now available in your choice of 3 endurance grades to suit your exact requirements:

**HIGH!  
EZ-ROLL™**

Tough wearing **Epsilon-Z™** Solid Bearing Raceway; a high tech/low friction alternative to needle-roller bearings. Standard for normally aspirated .842" dia. **Red-Zone™** Roller Lifters that see a maximum of 850 lbs. valve open spring force. For this grade, add "**EZ**" to the end of the **Red-Zone™** Roller Lifter part number when ordering. Captive guide bar feature automatically included.

**HIGHER!  
EZ-ROLLX™**

Upgraded **Epsilon-ZX™** Solid Bearing Raceway material; a super low friction, high-tech alternative to needles. Ideal for extreme loading environments where 900-1300 lbs. valve open spring force is employed, such as with turbo-supercharged/nitrous/all out normally aspirated & offshore marine applications. Now standard for all .904" & .937" dia. lifters and recommended for most .842 dia. offset pushrod seat lifter applications. For this grade, add "**EZX**" to the end of the **Red-Zone™** Roller Lifter part number when ordering. Includes captive guide bar feature.

**HIGHEST!!  
EZ-ROLLXP™**

Upgraded extreme loading **Epsilon-ZX™** Solid Bearing Raceway plus a unique DLC coated pin/axel... The ultimate in protection for sustained extreme loading environments such as suicide drag, long term endurance racing and super hard-core off shore marine applications. For this grade, add "**EZXP**" to the end of the **Red-Zone™** Roller Lifter part number when ordering. Includes captive guide bars. Available March, '08.

ROLL "EZ"....



.... **RED-ZONE™ Safe!**

ED ISKENDERIAN RACING CAMS

"Proudly leading the charge for the plain bearing revolution"

16020 SOUTH BROADWAY • GARDENA, CA 90247-9990 • (323) 770-0930 • FAX (310) 515-5730

www.iskycams.com